



# Coats Nylbond

Coats Nylbond is a bonded nylon thread made from pre-stabilised continuous filament nylon 6.6. It cuts cleanly at thread trimming with no ply separation and provides superior abrasion resistance in the sewn product.

BONDED  
CONTINUOUS  
FILAMENT  
NYLON 6.6

Product Information



## Main Uses:

- Leather footwear
- Leather goods
- Furniture Upholstery
- Automotive
- Luggage and travel goods
- Outdoor goods and sports equipment
- Protective footwear
- Filtration
- Computer contour stitching

## Why choose Nylbond?

- Coats Nylbond is a high tenacity nylon 6.6 for outstanding strength and durability.
- World class quality and superior abrasion resistance.
- Unique bond chemistry and proprietary coating technology produces a strong and supple thread with no ply untwisting, no flaking and no 'sewn in' colour change.
- Specially formulated lubricant for high temperature resistance and smooth operation through the needle eye without breaks, skips or staining.
- Controlled stretch characteristics for good loop formation and tight, firm and balances stitches
- Certified to Öko-Tex Standard 100.
- Meets Coats restricted substance list.

## Technical Services


Our team of experts deliver innovative solutions globally.





Tex	Ticket	Length	Strength cN	Elongation % Min - Max	Needle Size Metric
35	80	1000m	2160	15 - 26	90 - 110
45	60	1000m	3210	16 - 29	90 - 110
70	40	2500m	4700	16 - 29	100 - 120
105	30	2500m	6100	16 - 29	120 - 140
135	20	1000m	9500	17 - 29	130 - 160
180	15	1000m	13020	17 - 29	130 - 160
210	13	1000m	13330	17 - 31	140 - 180
270	10	1000m	18170	17 - 31	160 - 200
400	8	1000m	23090	17 - 32	180 - 230

Please refer to our information hub; footwear expertise section for further guidance:  
<http://www.coatsindustrial.com/en/information-hub/footwear-expertise>



Since conditions and applications vary considerably in the use of a product, the customer and/or user should assure herself or himself that the product meets end customer requirements and is suitable for the intended end use. Coats accepts no liability for unsuitable or improper use or application of products. Information provided above is based on current averages and should be taken only as indicative. Coats accepts no liability for the preciseness and correctness of the information provided. Product information sheets are updated from time to time, please be sure you are referring to the most recent publication. Coats supports customers with advice on individual applications on request; if you have any questions or concerns, please contact us.

