



LUX6 CE

Dimensions (approx.)

Chain width:	6 mm
Chain thickness:	2,4 mm
Single tape widths:	15 mm
Length of tape ends:	top: 20±2 mm bottom: 20±2mm

Features

Woven polyester tape;
available also in 100% cotton for post dyeing

Slider body out of die casted zinc,
puller out of zinc or punched steel

Chain members from: brass, copper,
nickel free, etc

Galvanic finishes: vast variety (pls.
see plating card)

Top stops and bottom stops with
members' finishing



Quality

Lateral strength	> 538 N
Lateral strength after reciprocation	> 485 N
Operating force	< 4 N
Reciprocation (durability)	> 500 cycles
Pull off strength of puller	> 245 N
Slider locking strength	> 78 N
Slider over top stops	> 117 N
Lateral strength of bottom stop	> 100 N
Slider against bottom stop	> 108 N

(The quality data represent minimum performance levels)

Main uses

High end jeans and trousers

High end skirts

High end knitwear

Luxury leather apparel

Luxury leather accessories

High end footwear

Luxury hand bags

Luxury luggage

Fastness

		Change	Staining
Washing 60° C	(ISO 105-C06)	4	4
Water	(ISO 105-E01)	4	4
Dry-cleaning	(ISO 105-D01)	4	3...4
Light	(ISO 105-B02)	5	
Rubbing wet	(ISO 105-X12)		3... 4
Rubbing dry	(ISO 105-X12)		4

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

EN 16732 – class C	CPSIA HR4040;
BS 3084:2006;	F963;
DIN 3416 – 19;	EN71;
Oeko-Tex 100 Class 1	QM System according BS EN ISO 9001:2008