



LUX6 2WCE O-form

Dimensions (approx.)

Chain width:	6 mm
Chain thickness:	2,4 mm
Single tape widths:	15 mm
Length of tape ends:	top: 21±4 mm bottom: 21±4mm

Features

Woven polyester tape;
available also in 100% cotton for post dyeing

Slider body out of die casted zinc,
puller out of zinc or punched steel

Chain members from: brass, copper,
nickel free, etc

Galvanic finishes: vast variety (pls.
see plating card)

Top stops and bottom stops with
members' finishing



Quality

Lateral strength	> 538 N
Lateral strength after reciprocation	> 485 N
Operating force	< 4 N
Reciprocation (durability)	> 500 cycles
Pull off strength of puller	> 245 N
Slider locking strength	> 117 N
Lateral strength of bottom stop	> 100 N
Slider against bottom stop	> 108 N

(The quality data represent minimum performance levels)

Main uses

Luxury leather accessories
Luxury hand bags
Luxury luggage

Fastness

		Change	Staining
Washing 60° C	(ISO 105-C06)	4	4
Water	(ISO 105-E01)	4	4
Dry-cleaning	(ISO 105-D01)	4	3...4
Light	(ISO 105-B02)	5	
Rubbing wet	(ISO 105-X12)		3... 4
Rubbing dry	(ISO 105-X12)		4

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

EN 16732 – class C	CPSIA HR4040;
BS 3084:2006;	F963;
DIN 3416 – 19;	EN71;
Oeko-Tex 100 Class 1	QM System according BS EN ISO 9001:2008