



### Dimensions (approx.)

Chain width:	6 mm
Chain thickness:	2,8 mm
Single tape widths:	16 mm
Length of tape ends:	top: 21±3 mm

### Features

Woven polyester tape; available also with marking points and interchangeable

Slider body out of die casted zinc, puller out of zinc

Moulded components made of POM (PolyOxyMethylene)

### P60 2WOE



### Quality

Lateral strength	> 392 N
Lateral strength after reciprocation	> 352 N
Operating force	< 4 N
Reciprocation test (durability)	> 500 cycles
Pull off strength of puller	> 245 N
Slider locking strength	> 49 N
Slider over bottom parts	> 90 N
Lateral strength of bottom end	> 147 N

(The quality data represent minimum performance levels)

### Main uses

Sportswear

Sweatshirts

Jogging suits

Work wear

Knitwear

Jackets and coats

Ski clothes

Leather goods

Sleeping bags

Outdoor goods

### Fastness

		Change	Staining
Washing 60° C	(ISO 105-C06)	4	4
Water	(ISO 105-E01)	4	4
Dry-cleaning	(ISO 105-D01)	4	3...4
Light	(ISO 105-B02)	5	
Rubbing wet	(ISO 105-X12)		3... 4
Rubbing dry	(ISO 105-X12)		4

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

### Standards

EN 16732 – class C	CPSIA HR4040;
BS 3084:2006;	F963;
DIN 3416 – 19;	EN71;
Oeko-Tex 100 Class 1;	QM System according BS EN ISO 9001:2008