



RT 25 CC

Dimensions (approx.)

Chain width	11 mm
Chain thickness	4,5 mm
Single tape widths	20 mm

Features

Sewn on polyester coil
Woven polyester tape



Quality

Lateral strength	> 979 N
Lateral strength after reciprocation	> 881 N
Reciprocation (durability)	> 500 cycles

(The quality data represent minimum performance levels)

Main uses
Outdoor goods
Frame tents
Awnings
Luggage
Rucksacks
Sportswear
Overalls

Fastness

		Change	Staining
Washing 60° C	(ISO 105-C06)	4	4
Water	(ISO 105-E01)	4	4
Dry-cleaning	(ISO 105-D01)	4	3...4
Light	(ISO 105-B02)	5	
Rubbing wet	(ISO 105-X12)		3...4
Rubbing dry	(ISO 105-X12)		4

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

EN 16732 – class D	CPSIA HR4040;
BS 3084:2006;	F963;
DIN 3416 – 19;	EN71;
Oeko-Tex 100 Class 1;	QM System according BS EN ISO 9001:2008



RT 25 CE

Dimensions (approx.)

Chain width	11 mm
Chain thickness	4,5 mm
Single tape widths:	20 mm

Features

Sewn on polyester coil
Woven polyester tape
Slider body out of die casted zinc, puller out of zinc



Quality

Lateral strength	> 979 N
Lateral strength after reciprocation	> 881 N
Reciprocation (durability)	> 500 cycles
Puller pull off strength	> 372 N
Slider locking strength	> 88 N
Operating force test	< 7 N
Slider over top stops	> 147 N
Lateral strength of bottom stop	> 180 N
Slider against bottom stop	> 176 N

(The quality data represent minimum performance levels)

Fastness

		Change	Staining
Washing 60° C	(ISO 105-C06)	4	4
Water	(ISO 105-E01)	4	4
Dry-cleaning	(ISO 105-D01)	4	3...4
Light	(ISO 105-B02)	5	
Rubbing wet	(ISO 105-X12)		3...4
Rubbing dry	(ISO 105-X12)		4

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

EN 16732 – class D	CPSIA HR4040;
BS 3084:2006;	F963;
DIN 3416 – 19;	EN71;
Oeko-Tex 100 Class 1;	QM System according BS EN ISO 9001:2008

Main uses
Outdoor goods
Frame tents
Awnings
Luggage
Rucksacks
Sportswear
Overalls



RT 25 OE

Dimensions (approx.)

Chain width	11 mm
Chain thickness	4,5 mm
Single tape widths:	20 mm

Features

Sewn on polyester coil
Woven polyester tape
Slider body out of die casted zinc, puller out of zinc



Quality

Lateral strength	> 979 N
Lateral strength after reciprocation	> 881 N
Reciprocation (durability)	> 500 cycles
Puller pull off strength	> 372 N
Slider locking strength	> 88 N
Operating force test	< 7 N
Slider over top stops	> 147 N
Lateral strength of open end	> 176 N
Box pull off strength	> 147 N

(The quality data represent minimum performance levels)

Fastness

Main uses
Outdoor goods
Frame tents
Sportswear
Overalls

		Change	Staining
Washing 60° C	(ISO 105-C06)	4	4
Water	(ISO 105-E01)	4	4
Dry-cleaning	(ISO 105-D01)	4	3...4
Light	(ISO 105-B02)	5	
Rubbing wet	(ISO 105-X12)		3...4
Rubbing dry	(ISO 105-X12)		4

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

EN 16732 – class D	CPSIA HR4040;
BS 3084:2006;	F963;
DIN 3416 – 19;	EN71;
Oeko-Tex 100 Class 1;	QM System according BS EN ISO 9001:2008



RT 25 2WOE

Dimensions (approx.)

Chain width	11 mm
Chain thickness	4,5 mm
Single tape widths:	20 mm

Features

Sewn on polyester coil
Woven polyester tape
Slider body out of die casted zinc, puller out of zinc



Quality

Lateral strength	> 979 N
Lateral strength after reciprocation	> 881 N
Reciprocation (durability)	> 500 cycles
Puller pull off strength	> 372 N
Slider locking strength	> 88 N
Operating force test	< 7 N
Slider over top stops	> 147 N
Lateral strength of bottom end	> 176 N
Slider over bottom parts	> 140 N

(The quality data represent minimum performance levels)

Fastness

Main uses
Outdoor goods
Frame tents
Sportswear
Overalls

		Change	Staining
Washing 60° C	(ISO 105-C06)	4	4
Water	(ISO 105-E01)	4	4
Dry-cleaning	(ISO 105-D01)	4	3...4
Light	(ISO 105-B02)	5	
Rubbing wet	(ISO 105-X12)		3...4
Rubbing dry	(ISO 105-X12)		4

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

EN 16732 – class D	CPSIA HR4040;
BS 3084:2006;	F963;
DIN 3416 – 19;	EN71;
Oeko-Tex 100 Class 1;	QM System according BS EN ISO 9001:2008