



S40 2WCE O-form Barrier slider

Dimensions (approx.)

Chain width:	4 mm
Chain thickness:	1,5 mm
Single tape widths:	12/16 mm
Length of tape ends:	top: 18±4 mm
	bottom: 18±4mm

Features

Woven polyester tape;
available also in Water repellent and
Flame retardant finish.

Both slider bodies (end fittings) &
Puller material - die casted zinc.

Top stops and bottom stops can be
metal or ultrasonically welded



Quality

Lateral strength	> 392 N
Lateral strength after reciprocation	> 353 N
Operating force	< 4 N
Reciprocation (durability)	> 500 cycles
Pull off strength of puller	> 90 N
Slider locking strength	> 20 N
Lateral strength of bottom stop	> 78 N
Slider against bottom stop	> 60 N

(The quality data represent minimum performance levels)

Main uses

Baby wear
Light leather goods
Pillows
Bed linen
Home textiles
Upholstered furniture
Luggage

Fastness

		Change	Staining
Washing 60° C	(ISO 105-C06)	4	4
Water	(ISO 105-E01)	4	4
Dry-cleaning	(ISO 105-D01)	4	3...4
Light	(ISO 105-B02)	5	
Rubbing wet	(ISO 105-X12)		3...4
Rubbing dry	(ISO 105-X12)		4

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

Oeko-Tex 100 Class 1;	CPSIA HR4040;
BS 3084:2006;	F963;
DIN 3416 – 19;	EN71;
QM System according BS EN ISO 9001:2008	