



S60 2WCE O-form Barrier slider

Dimensions (approx.)

Chain width:	6 mm
Chain thickness:	1,9 mm
Single tape widths:	16/21 mm
Length of tape ends:	top: 21±2 mm
	bottom: 21±2mm

Features

Woven polyester tape; also available in Water Repellent and Flame Retardant finish
Both slider bodies (end fittings) & Puller material - die casted zinc.
Top stop and bottom stops – metal



Quality

Lateral strength	> 783 N
Lateral strength after reciprocation	> 705 N
Reciprocation test (durability)	> 3000 cycles
Operating force	< 4 N
Puller pull off strength	> 245 N
Slider locking strength	> 49 N
Slider over top stops	> 117 N
Lateral strength of bottom stop	> 120 N
Slider against bottom stop	> 117 N

(The quality data represent minimum performance levels)

Main uses

Sportswear
Work wear
Overalls
Leather goods
Outdoor goods
Luggage
Hand bags
Sleeping bags
Home textiles
Automotive

Fastness

		Change	Staining
Washing 60° C	(ISO 105-C06)	4	4
Water	(ISO 105-E01)	4	4
Dry-cleaning	(ISO 105-D01)	4	3...4
Light	(ISO 105-B02)	5	
Rubbing wet	(ISO 105-X12)		3...4
Rubbing dry	(ISO 105-X12)		4

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

Oeko-Tex 100 Class 1;	CPSIA HR4040;
BS 3084:2006;	F963;
DIN 3416 – 19;	EN71;
QM System according BS EN ISO 9001:2008	