



### Dimensions (approx.)

Chain width:	8 mm
Chain thickness:	2,3+/-0.05 mm
Single tape widths:	17 mm

### Features

Woven polyester tape, coated on the back side with a specially formulated PU film. This coating renders the zips hydrophobic

### S80 CC HydroF



### Quality

Lateral strength	> 832 N
Lateral strength after reciprocation	> 749 N
Reciprocation test (durability)	> 3000 cycles
Operating force	< 7 N

(The quality data represent minimum performance levels)

### Main uses

Backpacks  
Luggage  
Mattresses  
Outdoor goods

### Fastness

		Change	Staining
Washing 60° C	(ISO 105-C06)	4	4
Water	(ISO 105-E01)	4	4
Dry-cleaning	(ISO 105-D01)	4	3...4
Light	(ISO 105-B02)	5	
Rubbing wet	(ISO 105-X12)		4
Rubbing dry	(ISO 105-X12)		3-4

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

### Standards

EN 16732 – class C	CPSIA HR4040;
BS 3084:2006;	F963;
DIN 3416 – 19	EN71;
Oeko-Tex 100 Class 1;	QM System according BS EN ISO 9001:2008