



Dimensions (approx.)

Chain width:	6 mm
Chain thickness:	2,4 mm
Single tape widths:	15 mm
Length of tape ends:	top: 22±2 mm bottom: 22±2mm

Features

Woven polyester tape
Slider body and puller out of die casted zinc
Welded top and bottom stops

S64 CE



Quality

Lateral strength	> 441 N
Lateral strength after reciprocation	> 396 N
Operating force	< 4 N
Reciprocation test (durability)	> 500 cycles
Pull off strength of puller	> 90 N
Slider locking strength	> 34 N
Slider over top stops	> 69 N
Lateral strength of bottom stop	> 60 N
Slider against bottom stop	> 59 N

(The quality data represent minimum performance levels)

Fastness

		Change	Staining
Washing 60° C	(ISO 105-C06)	4	4
Water	(ISO 105-E01)	4	4
Dry-cleaning	(ISO 105-D01)	4	3...4
Light	(ISO 105-B02)	5	
Rubbing wet	(ISO 105-X12)		3...4
Rubbing dry	(ISO 105-X12)		4

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

EN 16732 – class B	CPSIA HR4040
BS 3084:2006	F963
DIN 3416 –19	EN71
Oeko-Tex 100 Class 1	QM System according BS EN ISO 9001:2008

Main uses
Skirts
Dresses
Knitwear
Blouses
Ladies trousers
Medium weight fabrics
<i>Care should be taken with side seam/through the waistband styles to allow room for slider.</i>