



## FlamePro™ Splash

- Unbeatable protection, comfort and durability for people working in hazardous environments
- Inherently Flame & Heat Resistant
- Does not adhere onto skin and break open
- Low Charring
- CAT 2 Arc Protection

Technical Data	FlamePro™ Splash W340
Nominal Weight	10.0 osy (340 gsm)
Construction	Satin
Composition	FR Rayon, Nylon, Antistatic Fiber

Flame Resistance					
Arc Thermal Performance Value ASTM F1959	ATPV Rating PPE Category	15 cal/cm2 Category 2			
Heat & Flame Resistance	ISO 11612	Pass			
Molten Metal Splash ISO 9185	Molten Aluminum Rating Molten Iron Rating	D3 E3			
Time to Second Degree Burn	ASTM 955-15	No Burn			
Visual Rating of Fabric Exposed to Molten Aluminum	ASTM 955-15	Charring 1	Shrinkage 1	Adherence 1	Break Out 1

Available Colors	
Navy Blue	Orange

Since conditions and applications vary considerably in the use of a product, the customer and/or user should assure themselves that the product meets end customer requirements and is suitable for the intended end use. Coats accepts no liability for unsuitable or improper use or application of products. Information provided is based on current averages and should be taken only as indicative. Coats accepts no liability for the preciseness and correctness of the information provided. Please be sure you are referring to the most recent publication. Coats supports customers with advice on individual applications on request; if you have any questions or concerns, please contact us. © Copyright 2023.

