



LUX8 CC

Dimensions (approx.)

| | |
|---------------------|-------|
| Chain width: | 8 mm |
| Chain thickness: | 3 mm |
| Single tape widths: | 19 mm |

Features

Woven polyester tape;
available also in 100% cotton for post dyeing

Slider body out of die casted zinc,
puller out of zinc or punched steel

Chain members from: brass, copper,
nickel free, etc

Galvanic finishes: vast variety (pls.
see plating card)



Quality

| | |
|--------------------------------------|--------------|
| Lateral strength | > 734 N |
| Lateral strength after reciprocation | > 661 N |
| Operating force | < 6 N |
| Reciprocation (durability) | > 500 cycles |
| Member slippage strength | > 88 N |
| Member pull off strength | > 98 N |

(The quality data represent minimum performance levels)

Main uses

| |
|----------------------------|
| High end jeans |
| Luxury leather apparel |
| Luxury leather accessories |
| High end footwear |
| Luxury hand bags |
| Luxury luggage |

Fastness

| | | Change | Staining |
|---------------|---------------|--------|----------|
| Washing 60° C | (ISO 105-C06) | 4 | 4 |
| Water | (ISO 105-E01) | 4 | 4 |
| Dry-cleaning | (ISO 105-D01) | 4 | 3...4 |
| Light | (ISO 105-B02) | 5 | |
| Rubbing wet | (ISO 105-X12) | | 3... 4 |
| Rubbing dry | (ISO 105-X12) | | 4 |

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

| | |
|----------------------|---|
| EN 16732 – class D | CPSIA HR4040; |
| BS 3084:2006; | F963; |
| DIN 3416 – 19; | EN71; |
| Oeko-Tex 100 Class 1 | QM System according BS EN ISO 9001:2008 |



LUX8 CE

Dimensions (approx.)

| | |
|----------------------|--------------------------------|
| Chain width: | 8 mm |
| Chain thickness: | 3 mm |
| Single tape widths: | 19 mm |
| Length of tape ends: | top: 26±2 mm bottom: 25±2mm |

Features

Woven polyester tape;
available also in 100% cotton for post dyeing

Slider body out of die casted zinc,
puller out of zinc or punched steel

Chain members from: brass, copper,
nickel free, etc

Galvanic finishes: vast variety (pls.
see plating card)

Top stops and bottom stops with
members' finishing



Quality

| | |
|--------------------------------------|--------------|
| Lateral strength | > 734 N |
| Lateral strength after reciprocation | > 661 N |
| Operating force | < 6 N |
| Reciprocation (durability) | > 500 cycles |
| Pull off strength of puller | > 245 N |
| Slider locking strength | > 117 N |
| Slider over top stops | > 147 N |
| Lateral strength of bottom stop | > 240 N |
| Slider against bottom stop | > 100 N |

(The quality data represent minimum performance levels)

Main uses

High end jeans and trousers

High end skirts

High end knitwear

Luxury leather apparel

Luxury leather accessories

High end footwear

Luxury hand bags

Luxury luggage

Fastness

| | | Change | Staining |
|---------------|---------------|--------|----------|
| Washing 60° C | (ISO 105-C06) | 4 | 4 |
| Water | (ISO 105-E01) | 4 | 4 |
| Dry-cleaning | (ISO 105-D01) | 4 | 3...4 |
| Light | (ISO 105-B02) | 5 | |
| Rubbing wet | (ISO 105-X12) | | 3... 4 |
| Rubbing dry | (ISO 105-X12) | | 4 |

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

| | |
|----------------------|--|
| EN 16732 – class D | CPSIA HR4040; |
| BS 3084:2006; | F963; |
| DIN 3416 – 19; | EN71; |
| Oeko-Tex 100 Class 1 | QM System according BS EN ISO 9001:2008 |



LUX8 OE

Dimensions (approx.)

| | |
|----------------------|--------------|
| Chain width: | 8 mm |
| Chain thickness: | 3 mm |
| Single tape widths: | 19 mm |
| Length of tape ends: | top: 26±2 mm |

Features

Woven polyester tape;
available also in 100% cotton for post dyeing

Slider body out of die casted zinc,
puller out of zinc or punched steel

Chain members from: brass, copper,
nickel free, etc

Galvanic finishes: vast variety (pls.
see plating card)

Top stops and open end parts with
members' finishing



Quality

| | |
|--------------------------------------|--------------|
| Lateral strength | > 734 N |
| Lateral strength after reciprocation | > 661 N |
| Operating force | < 6 N |
| Reciprocation (durability) | > 500 cycles |
| Pull off strength of puller | > 245 N |
| Slider locking strength | > 117 N |
| Slider over top stops | > 147 N |
| Lateral strength of open end | > 157 N |
| Slider over open end | > 170 N |

(The quality data represent minimum performance levels)

Main uses

| |
|----------------------------|
| High end jackets |
| High end knitwear |
| Down outerwear |
| Luxury leather apparel |
| Luxury leather accessories |

Fastness

| | | Change | Staining |
|---------------|---------------|--------|----------|
| Washing 60° C | (ISO 105-C06) | 4 | 4 |
| Water | (ISO 105-E01) | 4 | 4 |
| Dry-cleaning | (ISO 105-D01) | 4 | 3...4 |
| Light | (ISO 105-B02) | 5 | |
| Rubbing wet | (ISO 105-X12) | | 3... 4 |
| Rubbing dry | (ISO 105-X12) | | 4 |

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

| | |
|----------------------|---|
| EN 16732 – class C | CPSIA HR4040; |
| BS 3084:2006; | F963; |
| DIN 3416 – 19; | EN71; |
| Oeko-Tex 100 Class 1 | QM System according BS EN ISO 9001:2008 |



LUX8 2WCE O-form

Dimensions (approx.)

| | |
|----------------------|--------------------------------|
| Chain width: | 8 mm |
| Chain thickness: | 3 mm |
| Single tape widths: | 195 mm |
| Length of tape ends: | top: 25±2 mm bottom: 25±2mm |

Features

Woven polyester tape;
available also in 100% cotton for post dyeing

Slider body out of die casted zinc,
puller out of zinc or punched steel

Chain members from: brass, copper,
nickel free, etc

Galvanic finishes: vast variety (pls.
see plating card)

Top stops and bottom stops with
members' finishing



Quality

| | |
|--------------------------------------|--------------|
| Lateral strength | > 734 N |
| Lateral strength after reciprocation | > 661 N |
| Operating force | < 6 N |
| Reciprocation (durability) | > 500 cycles |
| Pull off strength of puller | > 245 N |
| Slider locking strength | > 117 N |
| Lateral strength of bottom stop | > 100 N |
| Slider against bottom stop | > 137 N |

(The quality data represent minimum performance levels)

Main uses

| |
|----------------------------|
| Luxury leather accessories |
| Luxury hand bags |
| Luxury luggage |

Fastness

| | | Change | Staining |
|---------------|---------------|--------|----------|
| Washing 60° C | (ISO 105-C06) | 4 | 4 |
| Water | (ISO 105-E01) | 4 | 4 |
| Dry-cleaning | (ISO 105-D01) | 4 | 3...4 |
| Light | (ISO 105-B02) | 5 | |
| Rubbing wet | (ISO 105-X12) | | 3... 4 |
| Rubbing dry | (ISO 105-X12) | | 4 |

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

| | |
|----------------------|--|
| EN 16732 – class D | CPSIA HR4040; |
| BS 3084:2006; | F963; |
| DIN 3416 – 19; | EN71; |
| Oeko-Tex 100 Class 1 | QM System according BS EN ISO 9001:2008 |



LUX8 2WCE X-form

Dimensions (approx.)

| | |
|----------------------|--------------------------------|
| Chain width: | 8 mm |
| Chain thickness: | 3 mm |
| Single tape widths: | 19 mm |
| Length of tape ends: | top: 26±2 mm bottom: 26±2mm |

Features

| |
|--|
| Woven polyester tape; available also in 100% cotton for post dyeing |
| Slider body out of die casted zinc, puller out of zinc or punched steel |
| Chain members from: brass, copper, nickel free, etc |
| Galvanic finishes: vast variety (pls. see plating card) |
| Top stops and bottom stops with members' finishing |



Quality

| | |
|--------------------------------------|--------------|
| Lateral strength | > 734 N |
| Lateral strength after reciprocation | > 661 N |
| Operating force | < 6 N |
| Reciprocation (durability) | > 500 cycles |
| Pull off strength of puller | > 245 N |
| Slider locking strength | > 117 N |
| Slider over top stops | > 147 N |

(The quality data represent minimum performance levels)

Main uses

| |
|----------------------------|
| Luxury leather accessories |
| Luxury hand bags |
| Luxury luggage |

Fastness

| | | Change | Staining |
|---------------|---------------|--------|----------|
| Washing 60° C | (ISO 105-C06) | 4 | 4 |
| Water | (ISO 105-E01) | 4 | 4 |
| Dry-cleaning | (ISO 105-D01) | 4 | 3...4 |
| Light | (ISO 105-B02) | 5 | |
| Rubbing wet | (ISO 105-X12) | | 3... 4 |
| Rubbing dry | (ISO 105-X12) | | 4 |

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

| | |
|----------------------|--|
| EN 16732 – class D | CPSIA HR4040; |
| BS 3084:2006; | F963; |
| DIN 3416 – 19; | EN71; |
| Oeko-Tex 100 Class 1 | QM System according BS EN ISO 9001:2008 |



LUX8 2WOE

Dimensions (approx.)

| | |
|----------------------|--------------|
| Chain width: | 8 mm |
| Chain thickness: | 3 mm |
| Single tape widths: | 19 mm |
| Length of tape ends: | top: 26±2 mm |

Features

Woven polyester tape;
available also in 100% cotton for post dyeing

Slider body out of die casted zinc,
puller out of zinc or punched steel

Chain members from: brass, copper,
nickel free, etc

Galvanic finishes: vast variety (pls.
see plating card)

Top stops and open end parts with
members' finishing



Quality

| | |
|--------------------------------------|--------------|
| Lateral strength | > 734 N |
| Lateral strength after reciprocation | > 661 N |
| Operating force | < 6 N |
| Reciprocation (durability) | > 500 cycles |
| Pull off strength of puller | > 245 N |
| Slider locking strength | > 117 N |
| Slider over top stops | > 147 N |
| 2way open end box pull off | > 117 N |

(The quality data represent minimum performance levels)

Main uses

| |
|----------------------------|
| High end jackets |
| High end knitwear |
| Down outerwear |
| Luxury leather apparel |
| Luxury leather accessories |

Fastness

| | | Change | Staining |
|---------------|---------------|--------|----------|
| Washing 60° C | (ISO 105-C06) | 4 | 4 |
| Water | (ISO 105-E01) | 4 | 4 |
| Dry-cleaning | (ISO 105-D01) | 4 | 3...4 |
| Light | (ISO 105-B02) | 5 | |
| Rubbing wet | (ISO 105-X12) | | 3... 4 |
| Rubbing dry | (ISO 105-X12) | | 4 |

(These fastness grades represent minimum performance levels and, in practice, the majority of shades will exceed these levels)

Standards

| | |
|----------------------|---|
| EN 16732 – class C | CPSIA HR4040; |
| BS 3084:2006; | F963; |
| DIN 3416 – 19; | EN71; |
| Oeko-Tex 100 Class 1 | QM System according BS EN ISO 9001:2008 |